



*J D Jones & Co (P) Ltd*



## Pacmaan<sup>®</sup> NA 719

A high grade multipurpose braided packing made from expanded pure graphite yarns reinforced with a carbon fibre of high tensile strength for Power Plants, Refinery, Paper Plant, Mining & Metal, Chemical & Fertilizer Plants etc.

- One of the most versatile packings for plant wide pump and valve use,
- The outside corners of carbon yarns, make the packing one of the best performers for pumping applications even in high pressure.
- Certified as per API 589 / 607 7th Edition & ISO 10497:2010 fire safe test from Yarmouth Research and Technology, USA.
- Fantastic dry running capabilities—the packing is almost 'flushless'.
- Proven for regular as well as aggressive fluid services, including FCC catalyst, cooling water, pulp, super heated saturated steam etc.
- An inorganic corrosion inhibitor prevents stem pitting.

*Available in rope and ring form*

<b>Service Media and Conditions</b>	Caustics, water, steam, FCC catalyst and bottom slurry (refinery), DM water, all hydrocarbons, non-abrasive liquor, condensate, hypo, boiler feed water, fuel-lube oil, acid and alkali regeneration pumps
<b>Temperature*</b>	-240°C to 1000°C
<b>Pressure*</b>	345 bar
<b>Shaft Speed</b>	25 m/sec (rotary)
<b>pH</b>	0 to 14
<b>Applications</b>	Pumps, valves
	* Subjected to the media type